

Full Height TURNSTILE



Features:

- Access gate mechanic consist by two parts: frame and core .single reading device would be install on the frame, mail parts of core include motor, main board ,shift of the controller, fix poles, turnstiles supporting, turnstile, protection cover, fence, etc.
- Access direction: single or double direction (optional).prohibiting opposite direction passing, one side reading the card, the one side will lock when you passing forcely; the locking time can be
- Self resetting function the system will cancel the people passing right when the reading the card but not passing, the time can be set
- Prohibiting opposite direction passing
- Automatic function of opening or closing when the power off
- Direction indicator function ,showing passing or prohibiting for the people.
- Control board with counting function, LED digital display function (optional)
- Control board with memory function, can meet the groups pass through
- Without time delay require of the control signal thanks to adopt optical hole focus technology.

SPECIFICATION	S-FHT-1000
Power voltage	Ac220±10%, 50Hz
Open angle	90°
Drive voltage	AC12V+AC18V
Pass speed	≤30 Person/minutes
Operation condition	-15°C ~ +60°C
Structure	Frame or 304 Stainless steel cover
Relative humidity	None-condensati on
Open direction	Single and Double(optional)
Input signal	12v DC level or 12v pulse>100ms
Work environment	Outdoor and indoor
Working Current	≤2000mA
IP Degree	IP66
Length of the bar	600mm(optional)
Width of passage	≤630mm
Service life	≥6 million

