


10x High Speed Dome

Camera with Metal Housing IP66



Supported Browser



www.secureeye.com

KEY FEATURES

- 1.3 & 2MP Resolution
- 10x Optical Zoom
- 0 Lux/F1.4 Min. Illumination
- 128 Preset Position
- 60m IR Distance
- 4 Tour, 16 Preset position
- Metal Body Construction

SPECIFICATION		S-HSD-1AHD-10XM S-HSD-2AHD-10XM	
Camera	Sensor	1/3" HD CMOS Sensor	
	Lens	5 ~ 50mm	
	Optical Zoom	10x	
	Image Resolution	1280x960	1920x1080
	Minimum Illumination	Color: 0.5LUX / F1.4 (AGC ON), 0 LUX / F1.4 (IR ON)	
	Auto Day Night	On/Off	
	IR Range	60m	
	Exposure Mode	Auto/Shutter/Manual/IRIS/Bright	
System	Preset Position	128	
	Tour scan	4 tour, 16 preset position per tour, speed and dwell time, adjustable	
	Pattern Scan	4 pattern, 3 minutes recording for each pattern	
	Motion Detection	Yes	
	S/N Ratio	>50dB	
General	Shutter Speed	PAL: 1/50s -1/100,000s NTSC: 1/60s -1/100,000s	
	P/T/Z Control	Built-in RS485 P/T/Z control	
	Rotation Angle	Horizontal: 0° ~ 360°, Vertical: 0° ~ 90°	
	Rotation Speed	Horizontal: 1200 /s Vertical: 1200 /s	
	Synchronization	Internal	
	AGC	Auto	
	WDR	72dB	
	3D DNR	Auto / ON / OFF	
	BLC	Support	
	Privacy Zone	Yes	
	Frame Rate	25 / 30 fps	
	Operating Temperature	-10°C ~ 50°C	
	Power	DC12V 3A	
Housing	IP 66 & IK10		