

4 & 8 CHANNEL H.265+ NVR



SPECIFICATION		SIP-1S-2HDN-4	SIP-1S-2HDN-8
	Chipset	Hi3536D	
Video & Audio Input	IP Video Input	4ch	8ch
Video & Audio Output	HDMI	1ch, resolution:1920×1080/60Hz,1440×900/60Hz, 1280×1024/60Hz,1280×720/60Hz,1024×768/60Hz	
	VGA	1ch, resolution: 1920×1080/60Hz,1440×900/60Hz, 1280×1024/60Hz, 1280×720/60Hz, 1024×768/60Hz	
Recording	Compression	H.265+/H.265 /H.264+/H.264	
	Resolution	5MP /4MP / 3MP /1080P /720P /D1/CIF /QCIF	
Playback & Backup	Playback Mode	Smart/ Normal/ Time Division/ Label/ Event/ Picture/ Log Playback	
	Decoding Capability	4CH@1080P(25fps)	4CH@1080P(25fps)
	Backup Mode	USB Device/Network	
Advanced Features	Smart Detection	Line crossing, Area Intrusion, Fast moving, Unattached Object, Object Missing	
	Smart Playback	Line Crossing/Are Intrusion/Motion Detection	
	Cloud Storage	Support	
	Cloud Upgrade	Support	
Network	Incoming Bandwidth	30Mbps	40Mbps
	Outgoing Bandwidth	20Mbps	
	Ethernet	1 RJ-45 10 /100 Mbps self-adaptive Ethernet interface	
	Network Compatibility	HTTP, HTTPS, TCP/IP, IPv4, UPNP, RTSP, UDP, SMTP, NTP, DHCP, IP Filter, DDNS, FTP, P2P, ONVIF 2.6	
	Smart Phone	IOS(iPhone, iPad), Android(Phone, Pad)	
Hard Disk	SATA	1 SATA interface	
	Capacity	Up to 8TB capacity for each HDD	
External Interface	USB Interface	Front panel: 1 × USB 2.0 / Rear panel: 1 × USB 2.0	
General	Power Supply	DC12V/1.5A	
	Power Consumption	≤ 10W(without HDD)	
	Working Environment	-10°C~+55°C / 10%~90%RH	
	Dimension (W×D×H)	250x230x45mm	
	Weight	≤ 1.5kg	


www.secureeye.com