

HD-IP IR SPEED DOME MEDIUM CAMERA

With
Starlight
TECHNOLOGY



Audio Compression



Lightning Protection



Support P2P function



**IR Distance
Up to 240 Meters**



Video Compression



Power

Features

- Support P2P function, H.265
- 7" Half Metal Body Construction, IP66
- Optional function: Audio, TF Card Slot
- 9PCS IR LED + 4PCS Laser LED
- IR Range up to 240M
- ONVIF Compliant
- Intelligent IR illumination & power consumption is variable, dependant the zoom factor

5MP

RESOLUTION



PAN / TILT



AUTO FLIP

SPECIFICATION

S-PTZ-D5IP-20X-240M

Sensor	1/2.8" CMOS 5MP Hi3516E+Sony335
Output pixel	2592x1944@15fps / 2592x1520@22fps
Lens	20X, F=4.7-96.3mm
BLC	Support
AGC	Auto/Manual
WB	Indoor/Outdoor/Auto/Manual
DNR	2DNR,3DNR
WDR	DWDR
S/N Ratio	≥50dB
Lightning Protection	Transient voltage 6000V
Auto Control IR LED	PWM
LEDs	9PCS IR LED + 4PCS Laser LED
IR distance	Up to 240 meters
Communications Protocol	TCP/IP, HTTP, NTP, IGMP, DHCP, UDP, SMTP, RTP, RTSP, ARP, DDNS, DNS, HTTPS, P2P
Software Control	IE, CMS, Management Platform, P2P
Mobile View(optional)	Android , iPhone
Rotation range	Pan:0~360°,Tilt:0~93°
Rotation speed	Pan:0~80°/s, Tilt:0~40°/s
Auto Flip	Horizontal 180°,Vertical 93°
Preset Points	220pcs presets(dwll time 01-60s interval available)
A-B scan	User programmable (Speed 1-64 levels setting available)
Guard Tours	3 groups (Max.16 points, dwell time user selectable)
Video compression	H.265/H.264/M-JPEG
Audio compression	G711~PCM
Operating temperature	-40°C~+60°C
Power	DC 12V 4A
Consumption	≤25W
Related validation	IP66,CE,FCC,RoHs

ONVIF
COMPLIANT

